

## OVA38504E

Quick Signal – znak izlaza u slučaju nužde –  
standardan – trajan spoj – 1 h



### Glavno

Range	Exiway
Product name	Quick Signal
Product or component type	Emergency exit sign
Device application	Signalling
Function	Standard
Supply	Maintained
Colour	White
Light source colour	White
Provided equipment	Bracket wall/flag installation
Cover type	Transparent

### Komplementarno

Range compatibility	Remote control
[Ue] rated operational voltage	200...230 V AC/DC at 50 Hz
Power consumption in VA	8.5 VA
Current consumption	17 mA
Electrical insulation class	Class II
Battery capacity	0.6 AH 4.8 V Ni-Cd (Nickel-Cadmium)
Autonomy	1 h
Charging time	12 h
Bulb type	LED 100000 h
Luminous flux	Maintained mode: 14 lm Emergency condition: 12 lm
Visibility distance	28 m
Signalling function	Two sides indicator
Material	Housing: plastic Cover: plastic
Device mounting	Flush Surface ceiling Surface wall Hanging ceiling Flush false ceiling Flag type bracket wall
Height	235 mm
Width	290 mm
Depth	60 mm
Product weight	0.8 kg

### Okolina

IP degree of protection	IP40
IK degree of protection	IK07
ambient air temperature for operation	0...40 °C
fire resistance	850 °C
standards	EN 1838 EN 60598-2-22 IEC 50-11 IEC 695-2-1 EN 60695-2-10

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1101 - Schneider Electric declaration of conformity	Compliant - since 1101 - Schneider Electric declaration of conformity
Reference contains SVHC above the threshold - go to CaP for more details	Reference contains SVHC above the threshold
Available	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------