

## OVA38505E

Quick Signal – znak izlaza u slučaju nužde –  
standardan – trajan spoj – 3 sata



### Glavno

|                           |                                |
|---------------------------|--------------------------------|
| Range                     | Exiway                         |
| Product name              | Quick Signal                   |
| Product or component type | Emergency exit sign            |
| Device application        | Signalling                     |
| Function                  | Standard                       |
| Supply                    | Maintained                     |
| Colour                    | White                          |
| Light source colour       | White                          |
| Provided equipment        | Bracket wall/flag installation |
| Cover type                | Transparent                    |

### Komplementarno

|                                |  |
|--------------------------------|--|
| Range compatibility            | Remote control   |
| [Ue] rated operational voltage | 200...230 V AC/DC at 50 Hz   |
| Power consumption in VA        | 4.1 VA   |
| Current consumption            | 17 mA  |
| Electrical insulation class    | Class II   |
| Battery capacity               | 1.5 AH 4.8 V Ni-Cd (Nickel-Cadmium)  |
| Autonomy                       | 3 h  |
| Charging time                  | 24 h   |
| Bulb type                      | LED 100000 h   |
| Luminous flux                  | Maintained mode: 14 lm<br>Emergency condition: 12 lm   |
| Visibility distance            | 28 m   |
| Signalling function            | Two sides indicator  |
| Material                       | Housing: plastic<br>Cover: plastic   |
| Device mounting                | Flush<br>Surface ceiling<br>Surface wall<br>Hanging ceiling<br>Flush false ceiling<br>Flag type bracket wall |
| Height                         | 235 mm   |
| Width                          | 290 mm   |
| Depth                          | 60 mm  |
| Product weight                 | 0.9 kg   |

### Okolina

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP40  |
| IK degree of protection               | IK07  |
| ambient air temperature for operation | 0...40 °C   |
| fire resistance                       | 850 °C  |
| standards                             | EN 1838<br>EN 60598-2-22<br>IEC 50-11<br>IEC 695-2-1<br>EN 60695-2-10 |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Offer Sustainability

|  |   |
|--|---|
| Not Green Premium product  | Not Green Premium product   |
| Compliant - since 1101 - Schneider Electric declaration of conformity    | Compliant - since 1101 - Schneider Electric declaration of conformity |
| Reference contains SVHC above the threshold - go to CaP for more details | Reference contains SVHC above the threshold                           |
| Available  | Available   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|