



Glavno

Range of product	Jodiolux
Product or component type	Portable emergency lamp
Device application	Lighting
Colour	Blue
Wiring device additional information	Colour filters included Long distance light beam with range of 300 m

Komplementarno

[Ue] rated operational voltage	230 V 50 Hz
Power consumption in VA	6.5 VA
Device composition	Charging unit
Battery capacity	7 AH 6 V Ni-Cd (Nickel-Cadmium)
Charging time	24 h
Bulb type	Halogen 10 W main lamp Incandescent 1.5 W auxiliary lamp
Autonomy	24 h auxiliary lamp 4 h main lamp
Luminous flux	1300 lm 2 m main lamp 4 lm 1 m auxiliary lamp
Operating mode	Main lamp : blinking Auxiliary lamp : blinking
Operating angle	210 ° horizontal
Enclosure material	Plastic
Electrical insulation class	Class II
Length	128 mm
Height	334 mm
Width	136 mm
Product weight	2.1 kg

Okolina

IP degree of protection	IP65
ambient air temperature for operation	-10...40 °C
standards	EN 60598-2-8 IEC 2.2

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1101 - Schneider Electric declaration of conformity	Compliant - since 1101 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------

