

OVA41436E

Guardian–blok svjetla u slučaju nužde–standardan–
pripravan spoj–1 sat–1050 lm



Glavno

Range	Exiway
Product name	Guardian
Product or component type	Emergency light fitting
Device application	Lighting
Function	Standard
Supply	Non-maintained
Colour	Black
Light source	2 halogen x 50 W GY6.35
Light source colour	White
Cover type	Transparent
Number of batteries	1 x 12 V 7.2 AH lead-acid battery
Wiring device additional information	Searchlights rotate on their axis from 90° to 45° Can be inhibited with rest mode via Teleur range of remote controls

Komplementarno

[Ue] rated operational voltage	200...230 V AC/DC at 50 Hz
Power consumption in VA	37 VA
Current consumption	160 mA
Electrical insulation class	Class II
Autonomy	1 h
Charging time	12 h
Luminous flux	Emergency condition : 1050 lm
Material	Housing: plastic Cover: plastic
Device mounting	Surface ceiling Surface wall
Height	280 mm
Width	440 mm
Depth	230 mm
Product weight	7.5 kg
Market segment	Small commercial

Okolina

IP degree of protection	IP65
IK degree of protection	IK07
ambient air temperature for operation	0...40 °C
fire resistance	850 °C
standards	EN 60598-2-22 IEC 50-11 IEC 695-2-1 EN 60695-2-10

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0833 - Schneider Electric declaration	Compliant - since 0833 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

of conformity

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Contractual warranty

Warranty period

18 months
