

OVA43104E

Evx Ferro – komplet za spajanje – standardan – do
36 W – linijska montaža – 4 Ah



Glavno

| | |
|--------------------------------------|--|
| Range | Evx |
| Aesthetic name | Evx Ferro |
| Product or component type | Conversion kit |
| Function | Standard |
| Wiring device additional information | Can be inhibited with rest mode via remote control |

Komplementarno

| | |
|--------------------------------|---|
| [Ue] rated operational voltage | 230 V 50 Hz |
| Rated power in VA | 5 VA |
| Battery capacity | 4 AH 3.6 V Ni-Cd (Nickel-Cadmium) in line |
| Charging time | 24 h |
| Emergency luminous flux | 10 % of nominal flux during 1 h 30 32 W Gx24q 12 % of nominal flux during 1 h 30 32 W G10q 13 % of nominal flux during 2 h 18 W 2G11 13 % of nominal flux during 2 h 22 W G10q 14 % of nominal flux during 1 h 30 36 W 2G10 15 % of nominal flux during 1 h 28 W GR10q 15 % of nominal flux during 1 h 30 26 W G24q 16 % of nominal flux during 1 h 36 W 2G11 17 % of nominal flux during 2 h 11 W 2G7 17 % of nominal flux during 2 h 18 W G13 17 % of nominal flux during 2 h 18 W G24q 17 % of nominal flux during 2 h 30 24 W G5 fluorescent FHO T5 18 % of nominal flux during 1 h 36 W G13 20 % of nominal flux during 1 h 2 x 18 W G13 20 % of nominal flux during 1 h 30 28 W G5 fluorescent FHE T5 20 % of nominal flux during 3 h 10 W G24q 21 % of nominal flux during 2 h 13 W G24q 21 % of nominal flux during 3 h 9 W 2G7 22 % of nominal flux during 3 h 7 W 2G7 23 % of nominal flux during 1 h 30 16 W GR10q 23 % of nominal flux during 1 h 35 W G5 fluorescent FHE T5 24 % of nominal flux during 3 h 5 W 2G7 25 % of nominal flux during 2 h 10 W GR10q 25 % of nominal flux during 2 h 13 W G5 25 % of nominal flux during 2 h 21 W G5 fluorescent FHE T5 25 % of nominal flux during 2 h 30 14 W G5 fluorescent FHE T5 25 % of nominal flux during 3 h 8 W G5 26 % of nominal flux during 3 h 4 W G5 30 % of nominal flux during 3 h 6 W G5 32 % of nominal flux during 1 h 2 x 8 W G5 |
| Bulb type | Indicator LED |
| Ballast type | Electromagnetic ballast |
| Electrical insulation class | Class II |
| Connections - terminals | Screw terminals |
| Distance between centers | Circuit : 140 mm Battery : 210 mm |
| Height | Battery : 35 mm Circuit : 32.5 mm |
| Width | Circuit : 157 mm |
| Depth | Battery : 39 mm |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Circuit : 40.5 mm

| | |
|----------------|---------|
| Product weight | 0.65 kg |
|----------------|---------|

Okolina

| | |
|-----------------|--------|
| fire resistance | 850 °C |
|-----------------|--------|

| | |
|-----------|--|
| standards | IEC 695-2-1 EN 61347-2-7 IEC 34-50 IEC 50-11 EN 60695-2-10 EN 60924 |
|-----------|--|

Offer Sustainability

| | |
|-----------------------|-----------------------|
| Green Premium product | Green Premium product |
|-----------------------|-----------------------|

| | |
|---|---|
| Compliant - since 0833 - Schneider Electric declaration of conformity | Compliant - since 0833 - Schneider Electric declaration of conformity |
|---|---|

| | |
|---|---|
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
|---|---|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
