

## OVA43106E

Evx Ferro – komplet za spajanje – standardan – do  
58 W – linijska montaža – 4 Ah



### Glavno

Range	Evx
Aesthetic name	Evx Ferro
Product or component type	Conversion kit
Device application	Lighting
Function	Standard
Wiring device additional information	Can be inhibited with rest mode via remote control

### Komplementarno

[Ue] rated operational voltage	230 V 50 Hz
Rated power in VA	7 VA
Battery capacity	4 AH 3.6 V Ni-Cd (Nickel-Cadmium) in line
Charging time	24 h
Emergency luminous flux	10 % of nominal flux during 1 h 30 32 W G10q 10 % of nominal flux during 1 h 30 36 W 2G11 10 % of nominal flux during 1 h 40 W 2G11 10 % of nominal flux during 1 h 40 W G10q 10 % of nominal flux during 1 h 58 W G13 10 % of nominal flux during 2 h 36 W 2G10 11 % of nominal flux during 1 h 30 18 W G13 11 % of nominal flux during 2 h 32 W Gx24q 12 % of nominal flux during 1 h 30 26 W G24q 12 % of nominal flux during 1 h 36 W G13 13 % of nominal flux during 1 h 30 49 W G5 fluorescent FHO T5 13 % of nominal flux during 1 h 38 W GR10q fluorescent GE 14 % of nominal flux during 1 h 30 18 W G24q 18 % of nominal flux during 1 h 30 18 W 2G11 18 % of nominal flux during 1 h 30 2 x 18 W G13 18 % of nominal flux during 1 h 30 28 W GR10q 18 % of nominal flux during 2 h 30 24 W G5 fluorescent FHO T5 20 % of nominal flux during 1 h 35 W G5 fluorescent FHE T5 23 % of nominal flux during 2 h 21 W G5 fluorescent FHE T5 25 % of nominal flux during 1 h 30 13 W G24q 25 % of nominal flux during 2 h 2 x 8 W G5 25 % of nominal flux during 2 h 30 14 W G5 fluorescent FHE T5 33 % of nominal flux during 2 h 30 11 W 2G7 34 % of nominal flux during 3 h 9 W 2G7 7 % of nominal flux during 1 h 30 54 W G5 fluorescent FHO T5 8 % of nominal flux during 1 h 55 W 2G11
Bulb type	Indicator LED
Ballast type	Electromagnetic ballast
Electrical insulation class	Class II
Connections - terminals	Screw terminals
Device connection	Connection to remote switch
Distance between centers	Circuit : 140 mm Battery : 210 mm
Height	Battery : 35 mm Circuit : 32.5 mm
Width	Circuit : 157 mm
Depth	Battery : 39 mm Circuit : 40.5 mm
Product weight	0.65 kg

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

---

## Okolina

fire resistance	850 °C
standards	IEC 695-2-1 EN 61347-2-7 IEC 34-50 IEC 50-11 EN 60695-2-10 EN 60924

---

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0833 - Schneider Electric declaration of conformity	Compliant - since 0833 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

---

## Contractual warranty

Warranty period	18 months
-----------------	-----------

---