

Podatkovni list proizvoda

Karakteristike

PKE16M745

Utikač PratiKa, vijčani spoj – ravni – 16 A – 3P + N + E – 480...500 V AC – IP67



Glavno

Range	PratiKa
Product or component type	Wander plug
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

Komplementarno

Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	480...500 V
Network frequency	50/60 Hz
Ground lug clockwise position	7 h
Plug, socket material	Self-extinguishing engineering polymer housing:
Contacts material	Brass sleeves:
Connections - terminals	Captive screws
Cable cross section	1...4 mm ²
Cable outer diameter	8...15 mm
Cable entry	Cable gland Fair lead
Thread type	Pg 21
Product weight	0.22 kg
Height	142 mm
Width	89 mm
Depth	89 mm
Colour	Grey (RAL 7035)
Voltage colour	Black

Okolina

standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP67 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-11
relative humidity	50 % (40 °C) 70 % (30 °C) 90 % (20 °C)
operating altitude	2000 m
ambient air temperature for operation	35 °C (86400 s) -25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------

