

## Podatkovni list proizvoda

### Karakteristike

## PKE32M433

Utikač PratiKa, vijčani spoj – ravni – 32 A – 2P + E – 380...415 V AC – IP44



### Glavno

Range	PratiKa
Product or component type	Wander plug
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

### Komplementarno

Plug, socket, control station shape	Straight
[In] rated current	32 A
[Ue] rated operational voltage	380...415 V
Network frequency	50/60 Hz
Ground lug clockwise position	9 h
Plug, socket material	Self-extinguishing engineering polymer housing:
Contacts material	Brass sleeves:
Connections - terminals	Captive screws
Cable cross section	2.5...10 mm <sup>2</sup>
Cable outer diameter	11.5...21 mm
Cable entry	Cable gland Fair lead
Thread type	Pg 21
Product weight	0.2 kg
Height	152 mm
Width	76 mm
Depth	76 mm
Colour	Grey ( RAL 7035 )
Voltage colour	Red

### Okolina

standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-11
relative humidity	50 % ( 40 °C ) 70 % ( 30 °C ) 90 % ( 20 °C )
operating altitude	2000 m
ambient air temperature for operation	35 °C ( 86400 s ) -25...40 °C

### Contractual warranty

Warranty period	18 months
-----------------	-----------

