

Podatkovni list proizvoda

Karakteristike

PKF16M423

Utičnica PratiKa, vijčani spoj – ravna – 16 A – 2P + E
– 200...250 V AC – IP44



Glavno

Range	PratiKa
Product or component type	Wander socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

Komplementarno

Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Self-extinguishing engineering polymer housing:
Contacts material	Brass sleeves:
Connections - terminals	Captive screws
Cable cross section	1...4 mm ²
Cable outer diameter	8...15 mm
Cable entry	Cable gland Fair lead
Thread type	Pg 21
Product weight	0.16 kg
Height	78 mm
Width	78 mm
Depth	140 mm
Colour	Grey (RAL 7035)
Voltage colour	Blue

Okolina

standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	850 °C conforming to IEC 60695-2-1
relative humidity	50 % (40 °C) 70 % (30 °C) 90 % (20 °C)
ambient air temperature for operation	35 °C (86400 s) -25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------