

Podatkovni list proizvoda

Karakteristike

PKF32W735

Utičnica PratiKa–vijčana–pod kutom–32 A–3P + N + E–380... 415 V AC–zid



Glavno

| | |
|---------------------------|----------------|
| Range | PratiKa |
| Product or component type | Socket |
| Device short name | PratiKa socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Komplementarno

| | |
|-------------------------------------|---|
| Mounting mode | Wall-mounted |
| Plug, socket, control station shape | Angled |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 380...415 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Plug, socket material | Self-extinguishing engineering polymer housing: |
| Contacts material | Brass sleeves: |
| Connections - terminals | Captive screws |
| Cable cross section | 2.5...10 mm ² |
| Cable outer diameter | 21 mm |
| Thread type | M25 |
| Product weight | 0.41 kg |
| Height | 130 mm |
| Width | 106 mm |
| Depth | 154 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |

Okolina

| | |
|---------------------------------------|--|
| standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| fire resistance | 750 °C conforming to IEC 60695-2-1 |
| relative humidity | 50 % (40 °C) 70 % (30 °C) 90 % (20 °C) |
| ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.