

## Podatkovni list proizvoda

### Karakteristike

# PKX32W423

Utikač PratiKa–pod kutom–32 A–2P + E–200...250 V  
AC–IP44–montiran na zid



### Glavno

Range	PratiKa
Product or component type	Plug
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

### Komplementarno

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Self-extinguishing engineering polymer housing:
Contacts material	Nickel plated brass pins: Stainless steel screws:
Connections - terminals	Fast connection
Cable cross section	2.5...6 mm <sup>2</sup>
Cable outer diameter	21.5 mm
Thread type	M25
Product weight	0.27 kg
Base dimension	120 x 90 mm
Height	151 mm
Width	90 mm
Depth	89 mm
Colour	Grey ( RAL 7035 )
Voltage colour	Blue

### Okolina

standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
fire resistance	750 °C conforming to IEC 60695-2-11
pollution degree	3
relative humidity	50 % ( 40 °C ) 70 % ( 30 °C ) 90 % ( 20 °C )
ambient air temperature for operation	35 °C ( 86400 s ) -25...40 °C

### Contractual warranty

