

Podatkovni list proizvoda

Karakteristike

PKY32G714

Utičnica PratiKa – brza – ravna – 32 A – 3P + E – 100... 130 V AC – panel



Glavno

| | |
|---------------------------|----------------|
| Range | PratiKa |
| Product or component type | Socket |
| Device short name | PratiKa socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Network type | AC |
| Outlet standard | Industrial |

Komplementarno

| | |
|-------------------------------------|---|
| Mounting mode | Panel-mounted |
| Plug, socket, control station shape | Straight |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 100...130 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 4 h |
| Plug, socket material | Self-extinguishing engineering polymer housing: |
| Contacts material | Brass sleeves: |
| Connections - terminals | Fast connection |
| Cable cross section | 2.5...6 mm ² |
| Product weight | 0.22 kg |
| Base dimension | 90 x 100 mm |
| Height | 100 mm |
| Width | 95 mm |
| Depth | 127 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Yellow |

Okolina

| | |
|---------------------------------------|--|
| standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| fire resistance | 850 °C conforming to IEC 60695-2-1 |
| relative humidity | 50 % (40 °C) 70 % (30 °C) 90 % (20 °C) |
| ambient air temperature for operation | 35 °C (86400 s) |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
 Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu sadržanih informacija.