

PKY32M715

Utičnica PratiKa, vijčani spoj-ravna-32 A-3P + N + E-100...130 V AC-IP67



Glavno

| | |
|---------------------------|---------------|
| Range | PratiKa |
| Product or component type | Wander socket |
| Device short name | PratiKa fast |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Komplementarno

| | |
|-------------------------------------|---|
| Plug, socket, control station shape | Straight |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 100...130 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 4 h |
| Plug, socket material | Self-extinguishing engineering polymer housing: |
| Contacts material | Brass sleeves: |
| Connections - terminals | Fast connection |
| Cable cross section | 2.5...6 mm ² |
| Cable outer diameter | 11.5...21 mm |
| Cable entry | Cable gland |
| Thread type | Pg 21 |
| Product weight | 0.361 kg |
| Height | 104 mm |
| Width | 104 mm |
| Depth | 173 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Yellow |

Okolina

| | |
|---------------------------------------|--|
| standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| fire resistance | 850 °C conforming to IEC 60695-2-1 |
| relative humidity | 50 % (40 °C) 70 % (30 °C) 90 % (20 °C) |
| ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popununu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.