

PRA20424

Površinsko kućište Pragma – IP30 – 4 x 24 modula – bez vrata



Glavno

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	550 mm
Height	750 mm
Depth	148 mm
Number of 18 mm modules per row	24
Number of horizontal rows	4
Electrical insulation class	Class II Double insulation
Provided equipment	Marking kit (1) Terminal block (2) Identification label (1) Blanking plate strip (1)

Komplementarno

Enclosure mounting	Surface
9 mm pitches	48
Total number of 18 mm modules	96
Power dissipation in W	87 W
[In] rated current	160 A
Type of rail	Multifix
Cable entry	Cable or tube Cut-out plates Removable plates Trunking
Number of terminal blocks	1 earth terminal block with 32 Quick outgoers 1 neutral terminal block with 35 Quick outgoers
Distribution block outgoers	1 x 50 mm ² for earth 1 x 50 mm ² for neutral 28 x 6 mm ² for earth 28 x 6 mm ² for neutral 3 x 25 mm ² for earth 6 x 25 mm ² for neutral
Enclosure material	Back part: technoplastic Front face: technoplastic Back part: metal Front face: metal
Colour	Enclosure: white (RAL 9016) Front face: grey (RAL 7004)
Market segment	Residential Small commercial
Targeted country	Finland Sweden Baltic Greece Russia Hungary Czech republic

Okolina

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

fire resistance	Back part: 650 °C conforming to IEC 60695-2-1 Front face: 650 °C conforming to IEC 60695-2-1
IP degree of protection	IP30 without door conforming to EN/IEC 60529 IP40 with door conforming to EN/IEC 60529
IK degree of protection	IK08 without door conforming to EN/IEC 62262 IK09 with door conforming to EN/IEC 62262
overvoltage category	II
ambient air temperature for operation	-25...60 °C
standards	IEC 60670-24 IEC 60670-1 IEC 61439-1 IEC 61439-3 IEC 60998

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0810 - Schneider Electric declaration of conformity	Compliant - since 0810 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------