



Glavno

Network rated voltage	400 V - AC at 50 Hz 415 V - AC at 50 Hz
Reactive power rating	200 kvar
Operating mode	Automatic
Range	VarSet
Device short name	VarSet automatic
Product or component type	Capacitor bank

Komplementarno

Network pollution level	No polluted
[Gh/Sn] harmonic pollution rate	0...15 %
[THDU] total harmonic distortion	0...3 %
Power per step	25 kvar
Step composition	2x25 + 3x50
Location of connection	Top
Controller type	Varplus Logic VPL6 Modbus
Series name	EasyCan
Poles description	3P
Capacitance tolerance	- 5 % to 10 %
[Ui] rated insulation voltage	690 V
[Uimp] rated impulse withstand voltage	8 kV
Maximum permissible voltage	1.1 x Un (8 hours over 24 hours) conforming to IEC 60831
[Imp] maximum permanent current	Battery : 1.36 x In at 400 V conforming to IEC 61439-2 Battery : 1.36 x In at 400 V conforming to IEC 61439-2 Battery : 1.19 x In at 415 V conforming to IEC 61439-2 Capacitor : 1.5 x In at 480 V conforming to IEC 60831
Protection type	Without protection
[Icw] rated short-time withstand current	30 kA at 1 s (Icw)
Step protection type	Overload: harmonic control from VarPlus Logic Short-circuit: upstream protection
Accessibility for operation	Front
Colour	RAL 7035 (grey)
Product weight	131 kg
Height	1000 mm
Width	800 mm
Depth	300 mm
Provided equipment	Auxiliary transformer
Internal voltage transformer	400/230 V - 250 VA
Function available	GenSet shedding contact Alarm contact

Okolina

standards	IEC 61921 IEC 61439-2 IEC 61439-1
product certifications	ASEFA

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

CE
EAC

mounting location	Indoor
IP degree of protection	Environment: IP31
IK degree of protection	IK10
relative humidity	0...95 %
operating altitude	<= 2000 m
ambient air temperature for operation	-5...45 °C
average ambient air temperature for operation	Annual: 35 °C Over 24 hours: 45 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1325 - Schneider Electric declaration of conformity	Compliant - since 1325 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available