



### Glavno

|                               |                                 |
|-------------------------------|---------------------------------|
| Range                         | TeSys                           |
| Device short name             | VZ                              |
| Product or component type     | Additional pole                 |
| Performance level             | High performance                |
| Poles description             | 1P                              |
| Contacts type and composition | 1 NO                            |
| Product compatibility         | V0                              |
| Range compatibility           | TeSys VARIO switch disconnecter |
| Network type                  | AC<br>DC                        |
| Network frequency             | 50/60 Hz                        |
| Suitability for isolation     | Yes                             |

### Komplementarno

|  |   |
|--|---|
| Mounting location                            | Left  |
| [Ue] rated operational voltage               | 690 V AC 50/60 Hz   |
| [Uimp] rated impulse withstand voltage       | 8 kV  |
| [Ith] conventional free air thermal current  | 25 A  |
| [Ithe] conventional enclosed thermal current | 20 A  |
| Mechanical durability                        | 100000 cycles   |
| Electrical durability                        | 30000 cycles DC-1...5<br>100000 cycles AC-21  |
| Connections - terminals                      | Power circuit: screw clamp terminals cable 6 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Power circuit: screw clamp terminals cable 10 mm <sup>2</sup> - cable stiffness: solid |
| Tightening torque                            | Power circuit: 2.1 N.m - on screw clamp terminals   |
| Height                                       | 74 mm   |
| Width  | 16 mm   |
| Depth  | 35 mm   |
| Product weight                               | 0.05 kg   |

### Okolina

|                                       |  |
|---------------------------------------|--|
| standards                             | IEC 60947-3  |
| product certifications                | CSA<br>GL<br>UL  |
| protective treatment                  | TC   |
| IP degree of protection               | IP20 conforming to IEC 60529   |
| mechanical robustness                 | Vibrations 10...150 Hz 1 gn IEC 60068-2-6<br>Shocks 11 ms 30 Gn IEC 60068-2-27 |
| ambient air temperature for operation | -20...50 °C  |
| fire resistance                       | 960 °C conforming to IEC 60695-2-1   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.