

Podatkovni list proizvoda

Karakteristike

VZN11

TeSys Mini-VARIO – dodatni neutralni blok – 20 A – za VN12 / VN20



Glavno

| | |
|-------------------------------|--------------------------|
| Range | TeSys |
| Device short name | VZN |
| Product or component type | Additional neutral block |
| Performance level | Standard |
| Poles description | 1N |
| Contacts type and composition | 1 NO |
| Contact operation | Early make, late break |
| Product compatibility | VN12 VN20 |
| Network type | AC DC |
| Network frequency | 50/60 Hz |
| Mounting location | Right |

Komplementarno

| | |
|--|--|
| Range compatibility | TeSys , TeSys VARIO , VCFN , switch disconnecter |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 6 kV |
| [Ith] conventional free air thermal current | 20 A |
| [Ithe] conventional enclosed thermal current | 16 A |
| Mechanical durability | 50000 cycles |
| Electrical durability | 30000 cycles DC-1...5 50000 cycles AC-21 |
| Connections - terminals | Screw clamp terminals cable 4 mm ² - cable stiffness: flexible - with cable end cable end Screw clamp terminals cable 4 mm ² - cable stiffness: solid - |
| Tightening torque | 0.7 N.m - on screw clamp terminals |
| Height | 45.5 mm |
| Width | 12 mm |
| Depth | 39 mm |
| Product weight | 0.02 kg |

Okolina

| | |
|---------------------------------------|--|
| standards | IEC 60947-3 |
| product certifications | CSA GL UL |
| protective treatment | TC |
| IP degree of protection | IP20 conforming to IEC 60529 |
| mechanical robustness | Shocks 11 ms 15 gn IEC 60068-2-27 Vibrations 10...150 Hz 1 gn IEC 60068-2-6 |
| ambient air temperature for operation | -20...50 °C |
| fire resistance | 960 °C conforming to IEC 60695-2-1 |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|