

## XE2NP2161

kontaktni blok granične sklopke–1 NC + 1 NO–spori  
isklop, uklop prije isklopa



### Glavno

|                               |  |
|-------------------------------|--|
| Range of product              | OsiSense XC  |
| Series name                   | Standard format  |
| Product or component type     | Limit switch contact block                                   |
| Device short name             | XE2N   |
| Associated body               | ZCD26<br>ZCKJ6<br>ZCKJ6D<br>ZCKL6<br>ZCKM6<br>ZCKS6<br>ZCP26 |
| Number of poles               | 2  |
| Contacts type and composition | 1 NO + 1 NC  |
| Contact operation             | Slow-break, make before break                                |

### Komplementarno

|  |   |
|--|---|
| Product compatibility                  | XCKD<br>XCKJ<br>XCKL<br>XCKM<br>XCKP<br>XCKS  |
| Electrical connection                  | Screw-clamp terminals, clamping capacity: 1 x 0.5...2 x 2.5 mm <sup>2</sup>   |
| Contacts insulation form               | Zb  |
| Contacts material                      | Silver plated contacts  |
| Positive opening                       | With  |
| Minimum actuation speed                | 6 m/min   |
| Contact code designation               | Q300, DC-13 (U <sub>e</sub> = 250 V, I <sub>e</sub> = 0.27 A) conforming to EN/IEC 60947-5-1 appendix A<br>A300, AC-15 (U <sub>e</sub> = 240 V, I <sub>e</sub> = 3 A), I <sub>the</sub> = 10 A conforming to EN/IEC 60947-5-1 appendix A  |
| Resistance across terminals            | < 25 mOhm conforming to IEC 60255-7 category 3  |
| [Ui] rated insulation voltage          | 500 V degree of pollution 3 conforming to IEC 60947-1<br>300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14  |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1  |
| Short-circuit protection               | 10 A by gG cartridge fuse   |
| Electrical durability                  | 5000000 cycles, DC-13 120 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 24 V, 13 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 9 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |

### Okolina

### Offer Sustainability

|   |   |
|---|---|
| Green Premium product   | Green Premium product   |
| Compliant - since 0851 - Schneider Electric declaration of conformity | Compliant - since 0851 - Schneider Electric declaration of conformity |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Need no specific recycling operations

Need no specific recycling operations

---

### Contractual warranty

Warranty period

18 months

---