

Podatkovni list proizvoda**Karakteristike****XR2AB06K08**

1-stup. gran.sklopka s vijč.vezom XR2,za teške
uvjete—6 C/O–kućište od čel.lima

**Glavno**

| | |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Range of product | XR and XF |
| Product or component type | Single-stage heavy duty screw limit switch |
| Device short name | XR2 |
| Product specific application | Liquid level control in pumping systems Position control of moving parts of hoisting or materials handling equipment |
| Material | Sheet steel (enclosure) |
| Type of operator | Drive shaft, end fittings with sprocket key and washer |
| Maximum revolution speed | 25 rpm of input drive shaft |
| Theoretical number of turns | 0.8 of input drive shaft |
| Number of poles | 1 |

Komplementarno

| | |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mechanical durability | 10000000 cycles |
| Number of turns | <= 6 of threaded shaft |
| Threaded shaft screw pitch | 4 mm |
| Operating finger radius | 40 mm |
| Length of developed helical travel | 4 mm |
| Differential snap over angle | 30 ° contact actuators measured at finger |
| Repeat accuracy | 0.02 % on the tripping point |
| Number of teeth | 16 (pinion B) 26 (pinion D) 49 (pinion C) 59 (pinion A) |
| Actual number of turns | 0.863 (input drive shaft) |
| Contacts type and composition | 6 C/O |
| Contact operation | Snap action |
| [Ie] rated operational current | A300, AC-15 (Ue = 240 V, Ie = 3 A) conforming to EN/IEC 60947-5-1 Q300, DC-13 (Ue = 250 V, Ie = 0.27 A) conforming to EN/IEC 60947-5-1 |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 500 V conforming to EN/IEC 60947-1 600 V conforming to CSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-1 |
| Resistance across terminals | <= 25 MΩ |
| Short-circuit protection | 10 A cartridge fuse type gG |
| Connections - terminals | Screw clamp terminals, connection capacity: 2 x 1.5 mm ² with or without cable end Screw clamp terminals, connection capacity: 2 x 2.5 mm ² without cable end |
| Electrical durability | 10000000 cycles AC-15 50/60 Hz inductive at 12 V, 70 VA, operating rate 3600 cyc/h, load factor 0.5 EN/IEC 60947-5-1 10000000 cycles AC-15 50/60 Hz inductive at 127 V, 270 VA, operating rate 3600 cyc/h, load factor 0.5 EN/IEC 60947-5-1 10000000 cycles AC-15 50/60 Hz inductive at 220 V, 290 VA, operating rate 3600 cyc/h, load factor 0.5 EN/IEC 60947-5-1 10000000 cycles AC-15 50/60 Hz inductive at 24 V, 120 VA, operating rate 3600 cyc/h, load factor 0.5 EN/IEC 60947-5-1 10000000 cycles AC-15 50/60 Hz inductive at 380 V, 300 VA, operating rate 3600 cyc/h, load factor 0.5 EN/IEC 60947-5-1 10000000 cycles AC-15 50/60 Hz inductive at 48 V, 180 VA, operating rate 3600 cyc/h, load factor 0.5 EN/IEC 60947-5-1 10000000 cycles AC-15 50/60 Hz inductive at 500 V, 300 VA, operating rate 3600 cyc/h, load factor 0.5 EN/IEC 60947-5-1 10000000 cycles AC-15 50/60 Hz resistive at 12 V, 45 VA, operating rate 3600 cyc/h, |

0.5 EN/IEC 60947-5-1
 3000000 cycles DC-13 resistive at 220 V, 80 W, operating rate 3600 cyc/h, load factor 0.5
 0.5 EN/IEC 60947-5-1
 3000000 cycles DC-13 resistive at 24 V, 120 W, operating rate 3600 cyc/h, load factor 0.5
 0.5 EN/IEC 60947-5-1
 3000000 cycles DC-13 resistive at 440 V, 45 W, operating rate 3600 cyc/h, load factor 0.5
 0.5 EN/IEC 60947-5-1
 3000000 cycles DC-13 resistive at 48 V, 110 W, operating rate 3600 cyc/h, load factor 0.5
 0.5 EN/IEC 60947-5-1

| | |
|----------------|-----------------------|
| Cable entry | Removable gland plate |
| Product weight | 12 kg |

Okolina

| | |
|---------------------------------------|---------------------------------|
| standards | EN/IEC 60947-5-1 |
| protective treatment | TC |
| ambient air temperature for operation | -25...70 °C |
| ambient air temperature for storage | -40...70 °C |
| shock resistance | 50 gn for 11 ms |
| vibration resistance | > 5 gn (10...55 Hz) |
| IP degree of protection | IP54 conforming to EN/IEC 60529 |

Offer Sustainability

| | |
|-----------------------------|-----------------------------|
| Not Green Premium product | Not Green Premium product |
| Will be Compliant on 4Q2013 | Will be Compliant on 4Q2013 |
| | Will be Compliant on 4Q2013 |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|