

XUYAFVCO966S

fotoelektrični senzor – XUY – pojač. za vlakna – stakleni – 12..24 V DC – M8



Glavno

Range of product	OsiSense XU
Series name	Application assembly
Specific application of photoelectric detector	Detection in aggressive environments Detection of items exiting an oven (high temperature fibers) Detection of presence of parts in a plastic mould Monitoring position or presence of parts on an assembly or packing machine
Sensor name	XUY
Sensor design	Fiber design
Emission	Red LED

Komplementarno

Electronic sensor type	Photo-electric sensor
Material	Plastic
Enclosure material	Polycarbonate
Pulse frequency	8 kHz
Type of output signal	Discrete
Output type	Solid state
Discrete output function	1 NO or 1 NC programmable
Discrete output type	PNP and NPN
Electrical connection	1 male connector M8, 4 pins
Supply circuit type	DC
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply voltage limits	10...30 V DC
Voltage state 0 guaranteed	< 1.4 V
Voltage state 1 guaranteed	> 3 V
Switching capacity in mA	100 mA for overload and short-circuit protection
Switching frequency	< 1 kHz
Voltage drop	< 2 V (closed state)
Current consumption	<= 40 mA (no-load)
Delay response	<= 5 ms for glass fibre optics 3 mm
Delay recovery	<= 5 ms for glass fibre optics 3 mm
Setting-up	Sensitivity adjustment using +/- teach mode
Display type	Bar graph
Product weight	0.047 kg

Okolina

product certifications	CE CULus
ambient air temperature for operation	0...60 °C
ambient air temperature for storage	-20...80 °C
immunity to ambient light	<= 10000 lux with natural light <= 20000 lux with incandescent bulb
IP degree of protection	IP65 conforming to IEC 60529

Offer Sustainability

Not Green Premium product

Not Green Premium product

Compliant - since 0707 - Schneider Electric declaration of conformity Compliant - since 0707 - Schneider Electric declaration of conformity

Contractual warranty

Warranty period

18 months
