

XUYB954S

fotoelektrični senzor – XUY – polariziran – Sn 6 m –
12.. 24 V DC – priključci



Glavno

Range of product	OsiSense XU
Series name	Application, conveyor system and access control
Electronic sensor type	Photo-electric sensor
Sensor name	XUY
Sensor design	Compact
Detection system	Polarised reflex
Material	Plastic
Type of output signal	Discrete
Discrete output type	PNP and NPN
Discrete output function	1 NO or 1 NC programmable
Electrical connection	Screw terminal
Product specific application	Materials handling Access control Detection of belt breakage
Emission	Red
[Sn] nominal sensing distance	6 m

Komplementarno

Enclosure material	Polycarbonate
Output type	Solid state
Status LED	1 LED color: green for output status 1 LED color: red for alignment assistance 1 LED color: red for dirty optics 1 LED color: red for limit of detection 1 LED color: red for time delay 1 LED color: red for time function indicator
Supply voltage limits	20...250 V AC/DC
Voltage state 0 guaranteed	< 1.4 V
Voltage state 1 guaranteed	> 3 V
Switching capacity in mA	100 mA (overload and short-circuit protection)
Switching frequency	> 1000 Hz
Voltage drop	< 1 V at 10 mA (closed state) < 2 V at 100 mA (closed state)
Current consumption	50 mA (no-load)
Time delay range	0...10 s retriggerable delay for output circuit
Setting-up	Teach mode and/or fine manual adjustment
Product weight	0.13 kg

Okolina

product certifications	CE CULus
ambient air temperature for operation	0...60 °C
ambient air temperature for storage	-20...80 °C
immunity to ambient light	<= 10000 lux with incandescent bulb at 5° of optical axis <= 20000 lux with natural light at 5° to the optical axis
IP degree of protection	IP65 conforming to IEC 60529 IP67 conforming to IEC 60529

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0731 - Schneider Electric declaration of conformity	Compliant - since 0731 - Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months
-----------------	-----------
