

XUYPLCO966S

fotoelektrični senzor – XUY – difuzni – bočni – Sn 45 cm – 12..24 V DC – M8



Glavno

Range of product	OsiSense XU
Series name	Application
Electronic sensor type	Photo-electric sensor
Specific application of photoelectric detector	Control of presence of parts in container Detection of opaque or transparent parts Position or presence control of parts on assembling or conditioning machine
Sensor name	XUY
Sensor design	Compact
Material	Plastic
Detection system	Diffuse
Emission	Infrared
[Sn] nominal sensing distance	0...45 cm
Discrete output type	PNP/NPN
Electrical connection	4 pins M8 1 male connector
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Switching capacity in mA	100 mA for overload and short-circuit protection
Current consumption	< 40 mA (no-load)

Komplementarno

Enclosure material	Polycarbonate strong housing
Pulse frequency	8 kHz
Line of sight type	Lateral
Wiring technique	4-wire
Type of output signal	Discrete
Output type	Solid state
Supply circuit type	DC
Supply voltage limits	10...30 V DC
Switching frequency	<= 1 kHz
Voltage drop	< 1 V at 10 mA (closed state) < 2 V at 100 mA (closed state)
Delay response	< 500 μs
Delay recovery	< 500 μs
Setting-up	Parametering by buttons
Depth	13 mm
Length	78 mm
Width	30 mm

Okolina

product certifications	CE CULus
ambient air temperature for operation	0...60 °C
ambient air temperature for storage	-20...80 °C
immunity to ambient light	<= 10000 lux with incandescent bulb <= 20000 lux with natural light
IP degree of protection	IP65 conforming to IEC 60529

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period	18 months
-----------------	-----------
